



Window Into Construction

WinChem Middle East L.L.C
P.O.Box : 91107, Dubai, U.A.E.
Tel : +971 4 251 3818
Fax: +971 4 251 3667
Email : info@winchemme.com
Website : www.winchemme.com

WME Release Agent

Oil based shutter release agent

Product description

WME Release Agent is a specially formulated blend of mineral oils with a chemically active release agent that is suitable for application to mould and shutter faces prior to casting concrete in order to obtain a clean release.

Typical Applications& Advantages

- Ensure easy release, reducing damage and improving efficiency of production.
 - Reduces opportunity of damage to formwork, extending usable life.
 - Suitable for use with virtually all types of formwork.
-

Typical properties

Appearance	: Pale straw liquid
Specific Gravity	: Approximately 0.82
Chloride Content	: 0.01%

Features/benefits

- Allows clean , easy striking
 - Extends the life of formwork
 - Improved finish for fair faced concrete
 - Economical to use
 - Reduces blow hole formation
-

Technical support

WME provides a comprehensive technical support service to specifiers, end users and contractors and is able to offer on-site technical assistance.

Surface condition

Shutter surface must be clean and free from dirt and laitance

Application :

Apply one coat by brush, roller or spray. WME Release Agent is ready for use and requires no mixing. However, adequate stirring is advisable. Protect from rain.



Window Into Construction

Coverage

Depending on the porosity and texture of the mould surface approximately, coverage rate of 30 to 60 m²/litre/coat may be obtained.

Packaging

WME Release Agent is available in 200 litre drums or bulk supply.

Storage condition

Store in dry area in original containers between 5°C and 35°C .Protect from direct sunlight.

Shelf life

12 months minimum from production date, if stored properly in original unopened packing.

Cleaning

Clean all equipment and tools with detergent and luke warm water.

Health and safety information

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent material safety data sheet containing physical, ecological, toxicological and other safety-related data.

Legal note

The information, and, in particular, the recommendations relating to the application and end-use of WME products, are given in good faith based on WME's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with WME's recommendations. In practice, the differences in materials, substrates and actual site condition are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Users must always refer to the most recent issue of the product data sheet for the product concerned, copies of which will be supplied on request.

Rev: March, 2015

In Association with Kirton Concrete Services UK

UK Office
WinChem Construction Chemicals LTD.
Sydney Road, Watford,
WD 187QX
United Kingdom
Email: ukcorp@winchemme.com



Factory
WinChem Industries L.L.C.
P.O. Box: 3430, Umm Al Quwain, U.A.E.
Tel: +971 6 7667581
Fax: +971 6 7667582
Email : info@winchemind.com